

# ***Battle of the Rockets™ Competition 2020-2021***



Rev 1.0 Aug 8, 2020

## **Introduction**

The [Battle of the Rockets](#)™ is a program of the [Federation of Galaxy Explorers](#). The program is a series of competitive events focusing on the engineering design cycle. The events within the competition are designed to inspire student's interest in engineering and science with an exciting hands-on competition. The competition provides multiple levels of difficulty of engineering design challenges. These challenges are meant to continuously increase as the competitor's skill level grows. Each year, Galaxy Explorers will introduce new and more complex event challenges for the competition.

## **Dates**

Registration for the competition is due by Oct 30, 2020.

The launch will be held in April 2021 and will be for two days. If the pandemic is restricting travel for many teams, the target altitude event will be postponed until next year. The rover event will continue and require a demonstration of the rover via video conference.

## **The Competition**

The competition comprises multiple events. Each event has unique challenges and complexities. The events are judged separately.

## **Contact Information**

[rocketbattle.org](http://rocketbattle.org)

Federation of Galaxy Explorers

6404 Ivy Lane

Suite 810

Greenbelt, MD 20770

[battleoftherockets@gmail.com](mailto:battleoftherockets@gmail.com)

## Competition Operation

The competition starts when the competition guide is posted online in August. Teams can start designing before registration. Registration starts when the competition guide is posted and ends October 30.

All Target Altitude teams are required to submit rocket safety documents by the end of Dec 15. Documents will be reviewed and teams will receive comments about their designs. The purpose is to identify any potential safety or operation issues so teams will have a better chance of success. There will be a safety document template made available. Teams must include an email address for comments in the document and use the file name format as follows:

Safety\_XXXX.pdf where XXXX is the team number.

The sounding rocket event and rover event teams are required to submit PDR documents in December and have a review with judges. The PDR documents are scored. Teams will get score results after PDR.

February 1, sounding rocket event and rover event teams submit CDR documents and have a review with judges. The CDR documents are scored. Teams will get score results after CDR.

Templates for the PDR and CDR are provided. Use them and do not change the order of the slides. Scoring is based on the templates.

All rockets are to be flown before the competition weekend. Some documentation of a flight attempt should be submitted to the contest email. An example of documentation is a picture of the signed flight card.

PDR and CDR schedules are created by having volunteer judges sign up for time slots over a one week period indicating their availability for reviews. Time slots are in one hour increments from 7am until 8pm eastern. When two or three judges sign up for the same time slot, it becomes available for teams to select. At least one week before reviews start, the calendar of available time slots will be sent to the teams for selection. Each team is to submit 3 time slots and will be given the first available selected time slot. Reviews are to last a half hour.

In April, the competition launch will take place on Friday and Saturday. This allows dealing with weather issues and gives teams time to perform up to 3 qualifying launches and any test launches. There is no launch schedule for the two days. It is up to the teams to manage their time and get enough qualifying launches completed. The competition launch period starts 9am Friday, ends 5pm Friday, restarts 9am Saturday and ends 4pm Saturday. An awards ceremony will be held at 6pm Saturday at a to be determined facility. Teams do not need to be present. If not present, the award will be mailed to the team.

Weather can affect launching. NAR and Tripoli rules do not allow for launching into clouds or with winds over 20 mph. If the cloud ceiling is too low or the weather is affecting the performance of the rockets in any adverse way, the range will be shut down until the weather improves. The competition must follow all safety rules. It is possible the weather can affect the whole weekend. If rover and sounding rocket teams are not allowed to launch the whole weekend, awards will be given based on PDR and CDR scores. Target altitude teams will not be able to fly and will not receive any awards. Target altitude competition requirements will be kept the same for the next year.

### **Pandemic Alternative Judging**

If the pandemic has not improved by April and the local government is imposing restrictions on travel and/or crowd sizes, the launch will be cancelled. The target altitude event would be postponed until next year. Remote demonstrations of the deployable sensor payload and Mars rover will be required and judged. Demonstration procedures will be provided ahead of time along with the judging criteria. Shipment of payloads may also be required for judges to verify functionality. All payloads will be returned.

### **Launch Procedures**

All teams are to prepare their rockets and payloads in the team area. Teams must follow all safety procedures for handling rocket motors and ejection charges. When teams are ready to launch, they must bring their rocket to the Range Safety Officer (RSO) table for safety check. If performing a test flight, a club flight card needs to be filled out. For high power motors, a member of the team or mentor or any person over 18 and certified by NAR or Tripoli at the correct level must fill out the flight card. The RSO will check the rocket for flight worthiness and verify the rocket motor meets the 5:1 thrust to weight ratio.

Once approved by the RSO, the team with the certified motor handler will move on to the Launch Control Officer (LCO) at the flight line and hand off the flight card. The LCO will assign a launch pad and the team with the certified motor handler can proceed to load the rocket on the launch pad.

At the launch pad, the team can load the rocket and prepare the payload if the rocket has a payload. When it is time to arm the altimeter and insert the igniter, the non-certified team members must back away from the rocket. Only the minimal number of people should be near the rocket during the arming process and igniter insertion. Per range safety rules, no more than five people are allowed with a certified adult. All team members must return to the flight line after the rocket is ready for launch.

After all rockets have been launched, the LCO will announce the range is safe and at that time, teams can go into the field to recover their rockets and payloads.

Specific instructions for each event for recovery and judging are in each event section.

## Awards

Each event will have a set of awards. The top three teams will receive a plaque reflecting their ranking. If teams are not present during the award ceremony at the end of Saturday, the teams will be contacted and awards shipped.

All team members will receive certificates of participation. Teams must be present at the launch to receive the certificates.

## Launch Systems

Launch pads will be provided and have six foot long 1 inch (1010) aluminum rails. 8 foot 1.5 inch (1515) aluminum rails will be provided. The rails are to be vertical. They cannot be angled at all. Teams can substitute with their own launch equipment. Student launch equipment must be inspected before use for safety.

The following table is the rail requirements.

| <b>Rail</b> | <b>Max Motor Size</b> | <b>Rail Buttons</b> | <b>On Pad Max Weight (lb)</b> | <b>Max Rocket Diameter (in)</b> | <b>Rail Length (feet)</b> |
|-------------|-----------------------|---------------------|-------------------------------|---------------------------------|---------------------------|
| 1010        | J                     | 1010                | 15                            | 6.0                             | 6                         |
| 1515        | L                     | 1515                | 25                            | 7.5                             | 8                         |
| Unistrut    | O                     | Unistrut/1515       | 100                           | 18                              | 20                        |

## Practice Flights

Teams can perform test flights any time during the year up to the competition. The teams must perform test flights at sanctioned rocket launches supported by NAR or Tripoli. If testing with high power rocket motors, a team member must be certified or the team must find a person at the launch with proper certification to purchase and assemble the rocket motor for the team. Teams must follow all regulations when flying with high power rocket motors.

## Disqualifications

A team will be disqualified for any of the following reasons:

1. Recovery system does not deploy and the rocket free falls or comes in ballistic.
2. One or more parts of the rocket free fall from the rest of the rocket.
3. Rocket motor separates from the rocket during any part of flight.

4. Rocket is damaged beyond field repair after flight.
5. Team acts in a dangerous manner.
6. Team misbehaves and or interferes with other team's progress.
7. Team does not launch before the end of window.
8. Team attempts an unsafe recovery. An unsafe recovery is defined as attempting to remove any part of a rocket out of power lines or trees that require climbing. Rockets can be pulled out of trees or other vegetation if the team member can reach any part while standing on the ground.
9. Team argues with contest director.

## Rocket Test Flight

Teams are to complete one test flight and submit a flight document before the competition. Due to the complexity of some of the rockets, test flights must be completed before the competition.

Test flight information can be submitted electronically via email.

## Common Rules for All Events

| Item | Rule   |
|------|--|
| 1    | All competitors must follow the Tripoli High Power Safety Code. The code can be found on the Tripoli website. <a href="http://www.tripoli.org">www.tripoli.org</a> |
| 2    | The rocket must have been flown before. No first flight rockets are allowed.   |
| 3    | All rockets shall use a single motor: no clusters or staging allowed.  |
| 4    | The airframe, fins, nose cone, bulk plates, centering rings, and motor mount cannot be made of any metals.   |
| 5    | Metal fasteners and small metal components are allowed.  |
| 6    | Composite materials are allowed.   |
| 7    | Launch lugs are not allowed except for in the Target Altitude event.   |
| 8    | Competitors can provide their own launch pad and controller.   |
| 9    | A positive motor retention is required. Motor retention must pass RSO approval before the flight will be allowed.  |
| 10   | Friction fit of motors are not allowed.  |

|    |  |
|----|--|
| 11 | No modifications are allowed to any of the currently certified commercial motors. Manufacturers that allow modifications to the delay charge as part of standard assembly is allowed.  |
| 12 | Only currently certified NAR/Tripoli commercial motors are allowed.  |
| 13 | Average thrust to weight ratio must be at least 5:1. Rockets will not fly below that.  |
| 14 | Any of the commercially available altimeters are allowed.  |
| 15 | Electronic deployment devices are allowed. (dual deployment altimeters, Jolly Logic Chute release, etc.)   |
| 16 | Electronic deployment devices must be disarmed until the rocket is placed on the launch pad. Giant Leap Rocketry Slimshot and EFC are allowed to be configured as in the directions provided by the manufacturer.  |
| 17 | Recovery aids such as radio beacons/trackers and audible beacons are allowed.  |
| 18 | Maximum descent rate must not exceed 20 feet/sec.  |
| 19 | A recovery system is required so that the rocket lands and is immediately flyable without the need for any repairs or alterations. Rockets not meeting this definition will be disqualified.   |
| 20 | Any structural part of the rocket recovery system, or motor that free falls will result in a disqualification. Pop off rail guides are considered part of the ground support equipment. Any components that are supposed to be released or discarded for launch purposes are allowed. The competitor must specify what gets released or discarded for launch purposes before the launch. |
| 21 | The word of the safety committee and range safety officer is final. The safety team and/or RSO are the ultimate judges in determining a safe or unsafe flight.   |
| 22 | Rockets are not to exceed 10,000 feet due to waiver limits.  |
| 23 | Up to three attempts per competitor per event is allowed. Exceptions are due to malfunctioning launch equipment or faulty rocket motor due to manufacturer defects. Launch attempts stop at 4pm. It is up to the competitor to manage their time.  |
| 24 | Rockets may not use any externally-generated signals such as radio or computer control for any purpose, including flight termination, after liftoff. Autonomous on-board control systems can be used.  |
| 25 | No guidance systems are allowed.   |
| 26 | Boosted darts are not allowed.   |
| 27 | Recovery electronics must be turned on before the igniter is inserted.   |
| 28 | The igniter is to be installed at the launch pad when the rocket is in the vertical position.  |

|    |  |
|----|--|
| 29 | Competitors attempting unsafe recovery from trees or power lines will be disqualified. If a rocket lands in a tree or power line, an official must be notified to make a safe recovery.        |
| 30 | The altimeter used for altitude measurement must not be removed from the rocket or turned off until in the presence of a judge.  |
| 31 | If a team chooses to use a hybrid rocket motor, the team must provide all ground support equipment.  |
| 32 | No Li-PO batteries allowed.  |
| 33 | All electronics power must support up to an hour delay on the launch pad.  |
| 34 | No sparky motors or any type of motor that can generate sparks.  |
| 35 | If the rocket uses a level 1 or level 2 motor, at least one team member with the appropriate certification level must be present at the launch, handling the rocket and inserting the igniter. |
| 36 | The range safety officer has the right to refuse any rocket deemed not safe.   |
| 37 | If using VMAX rocket motor, electronic altimeter is required per manufacturer requirements.  |
| 38 | All parts of rockets must land safely.   |

# **Event 1: Mars Rover Mark III**

## Event 1: Mars Rover Mark III

The largest issue with this event is the condition of the terrain. The terrain is a farm field and crops vary from soybean to corn. If corn has been planted, expect the possibility of corn stocks. You need to design your rover to overcome cut corn stocks which can be as tall as a foot. Changes have been made to the rover requirements to allow some success if maneuvering becomes too difficult.

In the past, all rovers had some failure. Most failures were due to impacting the ground. The most common damage was to the wheels, axles and motor mounts.

This mission simulates a rover delivered to Mars and used as a tool by an astronaut who arrives later to the same location as the rover.

Design a rocket and Mars rover to launch to at least 1000 feet and deploy the Mars rover. The Mars rover must be fully contained in the rocket before being deployed. Once deployed, the Mars rover must return to the ground safely. Once landed, the rover shall autonomously disconnect or remove itself from any recovery device and travel 3 feet from the recovery device which will be used as a marker indicating the starting position. At the three foot mark, the rover shall stop and wait for a command.

The rover shall include a camera for taking still images and a manipulator to pick up an object. The manipulator needs to only be able to grasp an object and lift it off the ground so the rover can move without dragging the object. The object shall be placed on the ground no more than 3 feet from the rover after the rover completes its initial maneuvers after landing. The object will be a light-weight 3D printed cube with the dimensions of 3 inches on each side.

The team will designate a rover operator. The rover operator shall command the rover wirelessly with voice commands. The minimum commands required are to make the rover travel forward and reverse a specified distance. The distance measurement can be in any units including the number of rotations. The rover must be commanded to turn left or right and include commands to operate the camera and the manipulator. Speech recognition modules may be used as can laptops, tablets and cell phones. The judge will dictate what tasks are to be completed. The judge will ask for still images to be taken and ask for the object to be picked up and brought to the operator. Once operations commence, the operator cannot move from their position until all tasks are completed. Tasks include taking three still images and collecting the object and placing it at the foot of the operator. The still images must be displayed on whatever device is used for voice commanding.

## Rover Requirements

| Req # | Requirement  |
|-------|--|
| 1     | Rover cannot weigh more than 2 Kg.   |
| 2     | Rover must be contained completely inside the rocket during launch.  |
| 3     | The rover recovery system must be secured so no part of the rover free falls.                                |
| 4     | No pyrotechnics are allowed in the Mars rover.   |
| 5     | The rover shall take a still image when requested by the judge.  |
| 6     | Each image must be in color and have a resolution of at least 640x480  |
| 7     | At landing, the rover must release the recovery system. The recovery system can be used as the first marker. |
| 8     | Rover shall meet all operational requirements described.   |
| 9     | The rover must detach the parachute autonomously after landing.  |
| 10    | The rover must travel 3 feet within 10 minutes autonomously after detaching the parachute.                   |
| 11    | Mission must be completed in 5 minutes after commanding.   |
| 12    | No flying rovers.  |

## Controller Requirements

| Req# | Requirement   |
|------|---|
| 1    | Controller must accept voice commands.  |
| 2    | Controller must communicate with the rover via radio signals. WiFi, bluetooth or XBEE radio are allowed. XBEE radios must have their PAN/NET ID set to team number. |
| 3    | Controller must send a single command for each action required.   |
| 4    | Controller can be a laptop, tablet, cellphone or custom hardware.   |

## Rocket requirements

| Req # | Requirement   |
|-------|---|
| 1     | Motor clusters are not allowed.   |
| 2     | Staging is not allowed.   |
| 3     | Total installed impulse shall not exceed 2,560 Newton-seconds or a K motor.   |
| 4     | All parts of the rocket must safely return under a recovery system.   |
| 5     | The rocket airframe, nose cone, fins, bulk plates, and centering rings cannot be made of any types of metal. Composite materials are allowed.   |
| 6     | If the rocket with the rover exceeds 12 pounds, rail buttons for 1515 and extreme rails must be used.   |
| 7     | If the rocket is more than 6 inches in diameter, rail buttons for 1515 and extreme rails must be used.  |
| 8     | If the rocket is over 35 pounds or greater than 8 inches in diameter, unistrut rail buttons must be used and will be launched at the away cell. |
| 9     | The rocket must reach at least 1000 feet.   |
| 10    | The rocket must use a commercial altimeter for measuring the peak altitude.   |
| 11    | The average thrust to weight ratio must be greater than 5:1.  |
| 12    | Average thrust is per the motor designation. For example a J240 has an average thrust of 240 newton-seconds.                                    |
| 13    | The rocket must use a motor retainer. Friction fit is not allowed.  |
| 14    | All common rules must be followed.  |

## Documentation Requirements

Teams must submit a preliminary design review document and a critical design review document.

PDRs are due by December 1.

CDRs are due by February 1.

Documentation should be submitted via email to [battleoftherockets@gmail.com](mailto:battleoftherockets@gmail.com).

Templates will be provided for both PDR and CDR. Design review will be scheduled after each submission date. Teams will present via teleconference.

All documents must be in PDF format.

PDR file name format shall be `rover_xxxx_pdr.pdf` where `xxxx` is the team number.

CDR file name format shall be rover\_xxxx\_cdr.pdf where xxxx is the team number. The file name formats must be followed.

## Judging and Scoring

Before launch, teams must secure a judge. The judge must go out with the team during recovery to review the rover. No team member is allowed to touch the rover until the judge says it is OK or if the team decides the rover is nonfunctional. Any team member touching the rover forfeits all points toward the rover.

The judge must be at the site of the rover and monitor when the rover is commanded to collect a soil sample. The container must be removable so the judge can carry the sample back to the judging area and weigh the soil sample.

The team must bring the rocket to the judge with the altimeter so the judge can get the altitude reading for scoring. The altimeter must not be turned off before the judge gets the reading. Once the judge has completed scoring, the team may recover all parts of the rocket and payload.

## Flight Scoring

Teams will receive a score for each level successfully completed. Certain levels require previous levels and must be completed in order to gain current level points. The scores will be added to the PDR and CDR scores.

| Requirement | Score     | Function   |
|-------------|-----------|--|
| 1           | 50        | Rover mass does not exceed 2 Kg.   |
| 2           | 50        | Rover lands intact. No parts break off.  |
| 3           | Up to 360 | Rover travels 36 inches measured from the closest piece of recovery system to the back end of the rover. |
| 4           | 25        | Rover takes a still image (up to 3)  |
| 5           | 200       | Rover is voice commanded to retrieve the object and lift it off the ground.                              |
| 6           | 200       | Rover is voice commanded to bring the object to the  |

|   |     |   |
|---|-----|---|
|   |     | operator.   |
| 7 | 50  | Rover drops the object at the operator's feet on voice command. |
| 8 | 100 | Rocket reached 1000 feet or greater.                            |

# **Event 2: Deployable Sensor Payload**

## Event 2: Deployable Sensor Payload

Design a payload and rocket to launch to at least 800 feet and no more than 1300 feet and have the payload deploy from the rocket. The payload shall descend under helicopter recovery control and collect atmospheric data - air pressure, humidity and temperature. The position of the payload shall be tracked with GPS. A video camera shall be included that will take video of the ground and be spin stabilized so the video does not show a spinning landscape.

### Payload Requirements

| Req # | Requirement  |
|-------|--|
| 1     | Payload must not exceed 500 g.   |
| 2     | Payload must be deployed at apogee.  |
| 3     | The payload shall contain sensors to measure air pressure, humidity and temperature. |
| 4     | The position of the payload shall be tracked with GPS.                               |
| 5     | The payload shall transmit the sensor data to a ground station at 1 Hz rate.         |
| 6     | The payload shall use an XBEE radio at 2.4 GHz or 900 MHz                            |
| 7     | A video camera shall record the image of the ground during descent.                  |
| 8     | The video shall be spin stabilized so the rotation does not exceed +/- 15 degrees.   |
| 9     | The payload shall use helicopter recovery for descent.                               |

## Rocket requirements

| Req # | Requirement   |
|-------|---|
| 1     | Total installed impulse shall not exceed 160 Newton-Seconds or a G motor.                       |
| 2     | The rocket must reach at least 800 feet and not exceed 1300 feet.                               |
| 3     | The rocket must use a motor retainer. Friction fit is not allowed.                              |
| 4     | All common rules must be followed.  |
| 5     | The rocket must include an independent commercial altimeter to verify the rocket peak altitude. |

## Ground Station Requirements

| Req # | Requirement   |
|-------|---|
| 1     | The ground station shall be portable.                             |
| 2     | The ground station antenna shall be hand held.                    |
| 3     | The ground station shall operate on battery for at least 2 hours. |
| 4     | The ground station shall display the telemetry in real time.      |
| 5     | The ground station shall plot all sensor data in real time.       |

## Documentation Requirements

Teams must submit a preliminary design review document and a critical design review document.

PDRs are due by December 1.

CDRs are due by February 1.

Documentation should be submitted via email to [battleoftherockets@gmail.com](mailto:battleoftherockets@gmail.com).

Templates will be provided for both PDR and CDR. Design review will be scheduled after each submission date. Teams will present via teleconference.

All documents must be in PDF format.

PDR file name format shall be ds\_XXXX\_pdr.pdf where xxxx is the team number.

CDR file name format shall be ds\_XXX\_cdr.pdf where xxxx is the team number.

The file name formats must be followed.

## Judging and Scoring

Before launch, teams must secure a judge to be at the ground station. The judge will review the ground station and indicate when ready for launch. The team must also determine when they are ready for launch. One member of the team must be designated the mission control officer and must be positioned at the launch control officer and verify with their team they are ready for launch. The rocket will not be launched until the mission control officer gives word to launch.

After all parts of the rocket has been recovered, the team shall return the payload to the ground station and download the video with a judge present.

For altitude verification, the team must return the rocket with the altimeter still on. Do not turn off the altimeter before the judge records the altitude.

## Flight Scoring

The flight scores will be added to the PDR and CDR scores.

| Requirement | Points | Function  |
|-------------|--------|---|
| 1           | 50     | Rocket reaches at least 800 feet and does not exceed 1300 feet. |
| 2           | 50     | Payload deploys from the rocket.                                |
| 3           | 100    | Ground station receives telemetry and displays it in real time. |
| 4           | 250    | Ground station plots data in real time.                         |
| 5           | 50     | Video successfully captured.                                    |
| 6           | 300    | Video is spin stabilized.                                       |
| 7           | 0.1    | Per foot beyond 800 feet, not exceeding 1300 feet.              |
| 8           | 100    | Payload helicopter descent control works properly               |

# **Event 3: Target Altitude**

### Event 3: Target Altitude

Design and build a cone shaped vehicle to fly on any commercial certified F level rocket motor to as close to 350 feet as possible. The vehicle must be in the shape of a cone. The vehicle must have a height to diameter ratio of 1:1 or less. The height of the body cannot be more than the diameter not including any fins. Launch rods can be used due to the expected unique shape of the vehicle. The launch rod diameter shall be ¼ inch. For the recovery phase of the flight, the vehicle must use its drag to descend at a safe speed that does not damage the vehicle. Tumbling is not permitted. Parachutes and streamers are not permitted. The vehicle must carry a commercial altimeter.

The vehicle must safely recover and be in condition to be flown again. The team must perform two successful flights meeting all the requirements out of three attempts. Two attempts must meet the requirements or be disqualified. The team with the closest altitude to 350 feet wins.

The vehicle can be 3D printed or use any materials besides metal. The rocket must be test flown before the competition.

### Requirements

| Item | Requirement  |
|------|--|
| 1    | Two successful flights must be completed out of three attempts.  |
| 2    | Any commercial certified F motor is allowed.   |
| 3    | Only a commercial altimeter may be used.   |
| 4    | Minimum diameter of the vehicle shall be 5 inches.   |
| 5    | Height to diameter ratio of the vehicle body not including any fin shall not exceed 1:1.                     |
| 6    | If the vehicle requires a launch rod, it must support a ¼ inch launch rod.                                   |
| 7    | Vehicle must be designed and built from scratch. Cannot use kits or existing design files from the internet. |

## **Documentation Requirements**

Teams are required to submit a design document describing the design of the target altitude rocket by December 15. A document template will be provided. Documentation should be submitted via email to [battleoftherockets@gmail.com](mailto:battleoftherockets@gmail.com).

## **Judging and Scoring**

The scoring is the absolute value of  $350 - \text{altitude in feet}$ . The two best attempt scores will be summed and be the final score. Lowest score wins.

After teams complete a qualification flight attempt, the team must take their rocket with the altimeter to the judges tent to record the altitude. Do not turn off the altimeter until after the altitude has been recorded. The altitude must be recorded at the judge's tent.

## Application

Teams must submit an application form and identify each event to be attempted. The application form requires student information and a signed release form. No information will be released or sold. All applications are to be destroyed after the competition. The information requested are for administrative and insurance purposes only. The application fee for the Target Altitude event is \$50 and \$75 for the Sounding Rocket and Rover events. The application fee is nonrefundable. Teams can compete in more than one event.

## Team Requirements

Teams shall have at minimum 2 members and no more than 10 members per event. Teams can consist of university, college, or trade school students currently enrolled in a university, college, community college, high school, non-profit organizations such as boy scouts, girl scouts, 4-H club, etc or trade school. Each team must have a faculty advisor assigned to the team. The faculty advisor may support multiple teams. Teams can have a Tripoli or NAR certified mentor to review and guide teams in rocket design and motor handling.

**At least one Rover team member or mentor must have a membership in Tripoli or NAR and be certified at the proper level to use the selected high power rocket motors.**

Only team members can work on any aspect of the competition including the design, simulation, construction, repair, and launching. Adults, companies, and any non-team members cannot help. Mentors cannot design the rocket but can provide guidance in the design of the rocket and help with test launches.

## Team List Management

Each team must fill out an application which comprises of a spreadsheet that includes a list of team members. After submission and payment, the team members will receive their spreadsheet with team numbers for each event the team is participating in. The teams must maintain the list of team members and will submit the spreadsheet once more three weeks before the weekend launch with the final list of team members. The final list will be used for generating certificates and verifying submission of release forms.